

# CLEANING GUIDE

## Agglomerate Stone – Resin

**Classification:** Manufactured - Factory.

**Description:** Stone chips and piece matrix held together with a resin binder (typically epoxy).

**Density:** Medium.



**Porosity:** Slightly Porous (0.5% to 3.0%) to Moderately Porous (3.0% to 7.0%). Binder affects porosity.

**Uses:** Interior paving and wall applications.

**Other:** Most tiles will have the same characteristic as the stone used in the matrix.



## CLEANERS

DESIRED RESULTS	OMNI OPTIONS	BENEFITS	DILUTION RATIO	APPROX. COVERAGE	INT.	EXT.
PERIODIC SPRAY CLEANING		<ul style="list-style-type: none"> <li>• REMOVES LIGHT CONTAMINATES AND STAINS WITH MINIMAL EFFORT.</li> <li>• EFFECTIVE ON ALL WATER SAFE SURFACES.</li> <li>• PROVIDES LONG-LASTING, CLEAN ROSEMARY SCENT.</li> </ul>	FULL STRENGTH	33 - 100 SQ. FT. PER 32 oz	Yes	Yes
ROUTINE EVERYDAY CLEANING		<ul style="list-style-type: none"> <li>• HIGHLY CONCENTRATED FOR SAFE, COST EFFECTIVE, EVERYDAY CLEANING.</li> <li>• PROPRIETARY SURFACTANTS LIFT CONTAMINATES FROM WATER SAFE SURFACES.</li> <li>• REGULAR USE PRESERVES THE BEAUTY AND INTEGRITY OF THE SURFACE.</li> </ul>	1 - 4 oz PER GALLON WATER	5,000 - 10,000 SQ. FT. PER 70 oz	Yes	Yes
PERIODIC HEAVY DUTY CLEANING		<ul style="list-style-type: none"> <li>• VERSATILE ALKALINE FORMULA DILUTES W/WATER TO MATCH CLEANING NEEDS.</li> <li>• SAFELY REMOVES DIRT, GREASE, MOLD, SOAP SCUM, WAXES AND MORE.</li> <li>• LONG DWELL TIME FOR DIFFICULT CLEANING PROJECTS.</li> </ul>	4 - 64 oz PER GALLON WATER	75 - 10,000 SQ. FT. PER 70 oz	Yes	Yes
PROBLEM SOLVING CLEANING		<ul style="list-style-type: none"> <li>• “DUAL ACTION” CLEANING W/NANO SCRUBBING &amp; PROPRIETARY SURFACTANTS.</li> <li>• EFFECTIVE ON ALL WATER SAFE SURFACES.</li> <li>• THICK, CREAMY CONSISTENCY IS IDEAL FOR VERTICAL PROJECTS.</li> </ul>	FULL STRENGTH	200 – 2,000 SQ. FT. PER GALLON	Yes	Yes

**EXPERT TIP:** Some cleaning projects require more aggressive methods and products. See **OMNI Problem Solving Guide**. The Guide provides step-by-step instructions with a number of OMNI Options for the removal of contaminants and stains based on their nature and composition.

Technical Support: 949-709-5270 Mon thru Fri 6:00am PT to 4:00pm PT and/or E-mail [TechSupport@OMNI-Sealers.com](mailto:TechSupport@OMNI-Sealers.com).

Cleaning Guide is a general recommendation. Actual results may vary. Read product directions thoroughly before use.  
ALWAYS TEST IN A SMALL INCONSPICUOUS AREA.