

CLEANING GUIDE

Blue Stone

Classification: Geological. Metamorphic formation; siliceous.

Description: Composed of high percentage of silica particles compressed in layers and has a cleft texture.

Density: Hard (7 MOH).





Porosity: Non-Porous (<0.5%).

Uses: Interior walls and floors. Exterior paving and veneer (cladding).

Other: Available in flagstone and tile shapes.



CLEANERS

| DESIRED RESULTS | OMNI OPTIONS | BENEFITS | DILUTION RATIO | APPROX. COVERAGE | INT. | EXT. |
|------------------------------|---|---|----------------------------|----------------------------------|------|------|
| PERIODIC SPRAY CLEANING |  | <ul style="list-style-type: none"> REMOVES LIGHT CONTAMINATES AND STAINS WITH MINIMAL EFFORT. EFFECTIVE ON ALL WATER SAFE SURFACES. PROVIDES LONG-LASTING, CLEAN ROSEMARY SCENT. | FULL STRENGTH | 33 - 100 SQ. FT. PER 32 oz | Yes | Yes |
| ROUTINE EVERYDAY CLEANING |  | <ul style="list-style-type: none"> HIGHLY CONCENTRATED FOR SAFE, COST EFFECTIVE, EVERYDAY CLEANING. PROPRIETARY SURFACTANTS LIFT CONTAMINATES FROM WATER SAFE SURFACES. REGULAR USE PRESERVES THE BEAUTY AND INTEGRITY OF THE SURFACE. | 1 - 4 oz PER GALLON WATER | 5,000 - 10,000 SQ. FT. PER 70 oz | Yes | Yes |
| PERIODIC HEAVY DUTY CLEANING |  | <ul style="list-style-type: none"> VERSATILE ALKALINE FORMULA DILUTES W/WATER TO MATCH CLEANING NEEDS. SAFELY REMOVES DIRT, GREASE, MOLD, SOAP SCUM, WAXES AND MORE. LONG DWELL TIME FOR DIFFICULT CLEANING PROJECTS. | 4 - 64 oz PER GALLON WATER | 75 - 10,000 SQ. FT. PER 70 oz | Yes | Yes |
| PROBLEM SOLVING CLEANING |  | <ul style="list-style-type: none"> "DUAL ACTION" CLEANING W/NANO SCRUBBING & PROPRIETARY SURFACTANTS. EFFECTIVE ON ALL WATER SAFE SURFACES. THICK, CREAMY CONSISTENCY IS IDEAL FOR VERTICAL PROJECTS. | FULL STRENGTH | 200 - 2,000 SQ. FT. PER GALLON | Yes | Yes |

EXPERT TIP: Some cleaning projects require more aggressive methods and products. See **OMNI Problem Solving Guide**. The Guide provides step-by-step instructions with a number of OMNI Options for the removal of contaminants and stains based on their nature and composition.

Technical Support: 949-709-5270 Mon thru Fri 6:00am PT to 4:00pm PT and/or E-mail TechSupport@OMNI-Sealers.com.

**Cleaning Guide is a general recommendation. Actual results may vary. Read product directions thoroughly before use.
ALWAYS TEST IN A SMALL INCONSPICUOUS AREA.**