

CLEANING GUIDE

Limestone - Tumbled

Classification: Geological. Sedimentary formation; calcareous.

Description: Typical varieties exhibit minimal graining or directional movement.

Density: Medium to Hard (3 - 5 MOH).

Porosity: Moderately Porous (3.0% to 7.0%) to Highly Porous (>7.0%).

Uses: Interior walls, floors and countertops. Exterior limited to mild climate.

Other: Weathered finish achieved through tumbling stone w/sand, pebbles or steel bearings. May etch or lighten, if exposed to acid.



CLEANERS

| DESIRED RESULTS | OMNI OPTIONS | BENEFITS | DILUTION RATIO | APPROX. COVERAGE | INT. | EXT. |
|------------------------------|--------------|---|----------------------------|----------------------------------|------|------|
| PERIODIC SPRAY CLEANING | | <ul style="list-style-type: none"> REMOVES LIGHT CONTAMINATES AND STAINS WITH MINIMAL EFFORT. EFFECTIVE ON ALL WATER SAFE SURFACES. PROVIDES LONG-LASTING, CLEAN ROSEMARY SCENT. | FULL STRENGTH | 33 - 100 SQ. FT. PER 32 oz | Yes | Yes |
| ROUTINE EVERYDAY CLEANING | | <ul style="list-style-type: none"> HIGHLY CONCENTRATED FOR SAFE, COST EFFECTIVE, EVERYDAY CLEANING. PROPRIETARY SURFACTANTS LIFT CONTAMINATES FROM WATER SAFE SURFACES. REGULAR USE PRESERVES THE BEAUTY AND INTEGRITY OF THE SURFACE. | 1 - 4 oz PER GALLON WATER | 5,000 - 10,000 SQ. FT. PER 70 oz | Yes | Yes |
| PERIODIC HEAVY DUTY CLEANING | | <ul style="list-style-type: none"> VERSATILE ALKALINE FORMULA DILUTES W/WATER TO MATCH CLEANING NEEDS. SAFELY REMOVES DIRT, GREASE, MOLD, SOAP SCUM, WAXES AND MORE. LONG DWELL TIME FOR DIFFICULT CLEANING PROJECTS. | 4 - 64 oz PER GALLON WATER | 75 - 10,000 SQ. FT. PER 70 oz | Yes | Yes |
| PROBLEM SOLVING CLEANING | | <ul style="list-style-type: none"> "DUAL ACTION" CLEANING W/NANO SCRUBBING & PROPRIETARY SURFACTANTS. EFFECTIVE ON ALL WATER SAFE SURFACES. THICK, CREAMY CONSISTENCY IS IDEAL FOR VERTICAL PROJECTS. | FULL STRENGTH | 200 - 2,000 SQ. FT. PER GALLON | Yes | Yes |

EXPERT TIP: Some cleaning projects require more aggressive methods and products. See **OMNI Problem Solving Guide**. The Guide provides step-by-step instructions with a number of OMNI Options for the removal of contaminants and stains based on their nature and composition.

Technical Support: 949-709-5270 Mon thru Fri 6:00am PT to 4:00pm PT and/or E-mail TechSupport@OMNI-Sealers.com.

Cleaning Guide is a general recommendation. Actual results may vary. Read product directions thoroughly before use.
ALWAYS TEST IN A SMALL INCONSPICUOUS AREA.