

CLEANING GUIDE

Concrete Tile

Classification: Manufactured - Factory.

Description: Made w/variety of components incl. cement & aggregates (marble powder). Dry pressed or fired in a kiln.

Density: Medium.









Porosity: Moderately Porous (3.0% - 7.0%) to Highly Porous (>7.0%).

Uses: Interior walls, floors and countertops. Exterior applications limited to mild climate.

Other: Multiple texture options are available. May be susceptible to contaminants and stains.



CLEANERS

DESIRED RESULTS	OMNI OPTIONS	BENEFITS	DILUTION RATIO	APPROX. COVERAGE	INT.	EXT.
PERIODIC SPRAY CLEANING	 	<ul style="list-style-type: none"> REMOVES LIGHT CONTAMINATES AND STAINS WITH MINIMAL EFFORT. EFFECTIVE ON ALL WATER SAFE SURFACES. PROVIDES LONG-LASTING, CLEAN ROSEMARY SCENT. 	FULL STRENGTH	33 - 100 SQ. FT. PER 32 oz	Yes	Yes
ROUTINE EVERYDAY CLEANING	 	<ul style="list-style-type: none"> HIGHLY CONCENTRATED FOR SAFE, COST EFFECTIVE, EVERYDAY CLEANING. PROPRIETARY SURFACTANTS LIFT CONTAMINATES FROM WATER SAFE SURFACES. REGULAR USE PRESERVES THE BEAUTY AND INTEGRITY OF THE SURFACE. 	1 - 4 oz PER GALLON WATER	5,000 - 10,000 SQ. FT. PER 70 oz	Yes	Yes
PERIODIC HEAVY DUTY CLEANING	 	<ul style="list-style-type: none"> VERSATILE ALKALINE FORMULA DILUTES W/WATER TO MATCH CLEANING NEEDS. SAFELY REMOVES DIRT, GREASE, MOLD, SOAP SCUM, WAXES AND MORE. LONG DWELL TIME FOR DIFFICULT CLEANING PROJECTS. 	4 - 64 oz PER GALLON WATER	75 - 10,000 SQ. FT. PER 70 oz	Yes	Yes
PROBLEM SOLVING CLEANING	 	<ul style="list-style-type: none"> "DUAL ACTION" CLEANING W/NANO SCRUBBING & PROPRIETARY SURFACTANTS. EFFECTIVE ON ALL WATER SAFE SURFACES. THICK, CREAMY CONSISTENCY IS IDEAL FOR VERTICAL PROJECTS. 	FULL STRENGTH	200 - 2,000 SQ. FT. PER GALLON	Yes	Yes

EXPERT TIP: Some cleaning projects require more aggressive methods and products. See **OMNI Problem Solving Guide**. The Guide provides step-by-step instructions with a number of OMNI Options for the removal of contaminants and stains based on their nature and composition.

Technical Support: 949-709-5270 Mon thru Fri 6:00am PT to 4:00pm PT and/or E-mail TechSupport@OMNI-Sealers.com.

Cleaning Guide is a general recommendation. Actual results may vary. Read product directions thoroughly before use.

ALWAYS TEST IN A SMALL INCONSPICUOUS AREA.