

Efflorescence Remover

TECHNICAL DATA SHEET



PRODUCT BENEFITS:

- Unique Formulation that Removes and Inhibits the Reoccurrence of Efflorescence (natural water-soluble salts that can occur when cement based materials cure).
- Also Effectively Removes Mineral Oxide and other Inorganic Stains.
- Long Dwell Time for Difficult Projects.
- Non-Toxic. Non-Flammable. VOC Compliant. Biodegradable.
- Contains Distilled White Vinegar as a Natural Cleaning Boost.

USES:

- Tile, Most Stones, Concrete, Masonry and Grout Surfaces.
- Interior and Exterior applications.

DIRECTIONS:

Read entire label before using. Use only as directed. Always test in a small inconspicuous area to determine ease of application and desired results (see Limitations below).

APPLICATION STEPS:

1. Sweep or vacuum surface to be cleaned to remove any loose contaminants.
2. Apply a small amount of water to the surface to be cleaned.
3. Apply **Efflorescence Remover** liberally using a SpongaUSA™ sponge, or a mop, paint-pad applicator, paint roller, brush or low pressure pump sprayer.
4. Allow **Efflorescence Remover** to dwell for up to 10 minutes on surface.
5. Apply a second coat of **Efflorescence Remover** in same manner as step #3.
6. Allow second coat of **Efflorescence Remover** to dwell on surface for up to 10 minutes.
7. Agitate with a Primo Tools™ White Nylon Scrub Pad or other comparable non-marring scrubbing tool until efflorescence is removed from surface.
8. Thoroughly rinse surface with water. A wet/dry vacuum may also be used.
9. Some surfaces may require additional applications. **Expert Tip:** High-pressure (1000 – 3000 psi) sprayers are highly effective at rinsing away efflorescence stains when used in conjunction with **Efflorescence Remover**.
10. Wipe surface completely dry using a clean, dry, white cotton or micro-fiber towel.
11. If surface is to be sealed, allow 24 hours drying time prior to applying a high quality OMNI sealer (see OMNI Product Recommendation Guide).

SIZES:

Gallons (other sizes available by special order).

COVERAGE:

Approx. 50 to 250 sq. ft. (4.6m² to 23.2m²) per gallon depending on the type of surface, porosity, texture, temperature and method of application.

TECHNICAL SUPPORT:

Call 949-709-5270, Monday thru Friday, 6:00am PT to 4:00pm PT or e-mail TechSupport@OMNI-Sealers.com 24/7.

COMPLIANCE AND HANDLING:

- Complies with all Federal, State and Local VOC regulatory requirements.
- Use and store between 40°F and 100°F (4°C and 38°C).
- Store in original container only and close after each use.
- Shelf-life expected to be at least 1 year.

LIMITATIONS:

- May etch, lighten, or alter the color of cement based surfaces, metal, natural stone (such as marble, limestone and other acid sensitive stones) and tile.
- Do not mix with ammoniated cleaners or bleach as harmful fumes may result.
- Prevent product from contacting surrounding surfaces such as carpet, glass, landscaping, metal, paint and wood.

WARNINGS:

MAY BE HARMFUL IF SWALLOWED. MAY IRRITATE EYES AND SKIN. Wear skin and eye protection. If product gets in eyes, flush with water for at least 15 minutes. If product gets on skin, wash with soap and water. If irritation persists, seek medical attention. If swallowed, DO NOT induce vomiting, seek medical attention.

KEEP OUT OF REACH OF CHILDREN

WARRANTY:

100% SATISFACTION GUARANTEED, when used as directed. Contact OMNI Sealers for exclusive remedy of either refund of purchase price or replacement of product. Proof of purchase within one year of purchase, required. Determining suitability of product for intended use shall be solely the responsibility of the user. There are no warranties, expressed or implied, including those of merchantability or fitness for a particular purpose which is beyond the product description. In no case shall OMNI be liable for incidental or consequential damages.