

CLEANING GUIDE

Cement Grout

Classification: Manufactured – Job site.

Description: Mixture of cement, aggregates, additives & pigments. Sanded for wide joints (>1/8"). Unsanded for narrow joints (<1/8").

Density: Soft to Medium.

Porosity: Slightly Porous (0.5% to 3.0%) to Moderately Porous (3.0% to 7.0%).

Uses: Installed between Adjoining Tiles and Stones. Walls, Floors and Countertops. Interior and Exterior. Wet Areas.

Other: Sanded for wide joints (>1/8"). Unsanded for narrow joints (<1/8").



CLEANERS

DESIRED RESULTS	OMNI OPTIONS	BENEFITS	DILUTION RATIO	APPROX. COVERAGE	INT.	EXT.
PERIODIC SPRAY CLEANING		<ul style="list-style-type: none"> REMOVES LIGHT CONTAMINATES AND STAINS WITH MINIMAL EFFORT. EFFECTIVE ON ALL WATER SAFE SURFACES. PROVIDES LONG-LASTING, CLEAN ROSEMARY SCENT. 	FULL STRENGTH	33 - 100 SQ. FT. PER 32 oz	Yes	Yes
ROUTINE EVERYDAY CLEANING		<ul style="list-style-type: none"> HIGHLY CONCENTRATED FOR SAFE, COST EFFECTIVE, EVERYDAY CLEANING. PROPRIETARY SURFACTANTS LIFT CONTAMINATES FROM WATER SAFE SURFACES. REGULAR USE PRESERVES THE BEAUTY AND INTEGRITY OF THE SURFACE. 	1 - 4 oz PER GALLON WATER	5,000 - 10,000 SQ. FT. PER 70 oz	Yes	Yes
PERIODIC HEAVY DUTY CLEANING		<ul style="list-style-type: none"> VERSATILE ALKALINE FORMULA DILUTES W/WATER TO MATCH CLEANING NEEDS. SAFELY REMOVES DIRT, GREASE, MOLD, SOAP SCUM, WAXES AND MORE. LONG DWELL TIME FOR DIFFICULT CLEANING PROJECTS. 	4 - 64 oz PER GALLON WATER	75 - 10,000 SQ. FT. PER 70 oz	Yes	Yes
PROBLEM SOLVING CLEANING		<ul style="list-style-type: none"> "DUAL ACTION" CLEANING W/NANO SCRUBBING & PROPRIETARY SURFACTANTS. EFFECTIVE ON ALL WATER SAFE SURFACES. THICK, CREAMY CONSISTENCY IS IDEAL FOR VERTICAL PROJECTS. 	FULL STRENGTH	200 - 2,000 SQ. FT. PER GALLON	Yes	Yes

EXPERT TIP: Some cleaning projects require more aggressive methods and products. See **OMNI Problem Solving Guide**. The Guide provides step-by-step instructions with a number of OMNI Options for the removal of contaminants and stains based on their nature and composition.

Technical Support: 949-709-5270 Mon thru Fri 6:00am PT to 4:00pm PT and/or E-mail TechSupport@OMNI-Sealers.com.

Cleaning Guide is a general recommendation. Actual results may vary. Read product directions thoroughly before use.

ALWAYS TEST IN A SMALL INCONSPICUOUS AREA.