

Poultice Stain Remover

TECHNICAL DATA SHEET



PRODUCT BENEFITS:

- Highly Effective, Multi-Purpose Formulation Combines an Absorptive Clay to “Pull” Deep-Set, Below Surface Stains and a Fine Abrasive Powder to “Scrub Away” Surface Stains.
- Non-Toxic. Non-Flammable. VOC Compliant. Biodegradable.
- Contains Baking Soda to Help Eliminate Odors.

USES:

- Tile, Stone, Concrete, Masonry and Grout Surfaces.
- Can be Added to Most Cleaners to “Boost” their Effectiveness.
- Interior and Exterior applications.

DIRECTIONS:

Read entire label before using. Use only as directed.

APPLICATION STEPS:

Deep Set Stains

1. Mix **Poultice Stain Remover** with water to form a thick paste. Expert Tip: Depending on type of stain, can use an OMNI Cleaner or Remover in place of water for enhanced performance (see OMNI Product Recommendation Guide).
2. Apply **Poultice Stain Remover** paste approximately ¼” thick to stained surface. Allow paste to extend beyond the edges of the stain by at least 1”.
3. Cover paste with plastic and tape edges of plastic to surface with painter's-type tape.
4. Allow paste to dwell on surface for 24 to 48 hours.
5. Remove the plastic covering the paste.
6. Remove paste with a non-marring tool (plastic putty knife).
7. After stain has been removed, clean paste with a SpongaUSA™ Sponge, or a white, cotton or micro-fiber towel and water.
8. Thoroughly rinse surface with water & dry with a white cotton or micro-fiber towel. A wet/dry vacuum may also be used.
9. Some stains may require 2 or more applications.
10. If surface is to be sealed, allow 24 hours drying time prior to applying a high quality OMNI sealer (see OMNI Product Recommendation Guide).

Surface Stains

1. Apply a small amount of water to surface to be cleaned.
2. Liberally sprinkle **Poultice Stain Remover** to the wet surface and mix into thin slurry. Expert Tip: For stains on vertical surfaces, mix **Poultice Stain Remover** with water into slurry in a container, then applied to the wet surface.
3. Scrub surface with a Primo Tools™ White Nylon Scrub Pad or other comparable non-marring scrubbing tool until stain is removed. Expert Tip: For large stain surfaces, a low RPM (300-750 RPM) buffer can be used with a white nylon pad to remove stains. Keep surface wet during buffing process.
4. After stain has been removed, clean solution from surface with a SpongaUSA™ sponge, or a white cotton or micro-fiber towels and water. A wet/dry vacuum may also be used.
5. Thoroughly rinse surface with clean water and dry with a white cotton or micro-fiber towel.
6. Some stains may require 2 or more applications.
7. If surface is to be sealed, allow 24 hours drying time prior to applying a high quality OMNI sealer (see OMNI Product Recommendation Guide).

SIZES:

12 oz. Jar (other sizes available by special order).

COVERAGE:

Approx. 25 to 75 sq. ft. (2.3m² to 7.0m²) per 12 oz jar depending on the type of surface, porosity, texture, temperature and method of application.

TECHNICAL SUPPORT:

Call 949-709-5270, Monday thru Friday, 6:00am PT to 4:00pm PT or e-mail TechSupport@OMNI-Sealers.com.

COMPLIANCE AND HANDLING:

- Complies with all Federal, State and Local VOC regulatory requirements.
- Use and store between 40°F and 100°F (4°C and 38°C).
- Store in original container only and close after each use.
- Shelf life expected to be at least 1 year.

LIMITATIONS:

- Prevent product from contacting surrounding surfaces such as carpet, glass, landscaping, metal, paint and wood.

WARNINGS:

MAY BE HARMFUL IF SWALLOWED. MAY IRRITATE EYES AND SKIN. Wear skin and eye protection. If product gets in eyes, flush with water for at least 15 minutes. If product gets on skin, wash with soap and water. If irritation persists, seek medical attention. If swallowed, DO NOT induce vomiting, seek medical attention.

KEEP OUT OF REACH OF CHILDREN

WARRANTY:

100% SATISFACTION GUARANTEED, when used as directed. Contact OMNI Sealers for exclusive remedy of either refund of purchase price or replacement of product. Proof of purchase within one year of purchase, required. Determining suitability of product for intended use shall be solely the responsibility of the user. There are no warranties, expressed or implied, including those of merchantability or fitness for a particular purpose, which is beyond the product description. In no case shall OMNI be liable for incidental or consequential damages.