

Grout Release

TECHNICAL DATA SHEET



PRODUCT BENEFITS:

- Formulated to Provide a Temporary Water-Soluble Pre-grout Coating that Protects Surfaces from Mortar and Grout Stains.
- Makes the Installation and Cleanup of Grout Easier.
- Grout Clean-up Process Removes/Eliminates Coating.
- Non-Toxic. Non-Flammable. VOC Compliant. Biodegradable.

USES:

- Tile, Stone, Concrete, and Masonry Surfaces
- Ideal for Porous and/or Textured Surfaces such as Slate, Saltillo, Brick and Brick Pavers.
- Interior and Exterior applications.

DIRECTIONS:

Read entire label before using. Use only as directed. Always test in a small inconspicuous area with a 24-hour cure time to determine ease of application and desired results.

APPLICATION STEPS:

1. Apply **Grout Release** liberally using a SpongaUSA™ grout sponge, or a heavy-textured paint roller or brush.
2. Assure a thick, complete coating of surface, while preventing **Grout Release** build-up in grout joints.
3. Allow **Grout Release** to dwell at least 30 minutes on the surface until it becomes dry "to the touch".
4. Install grout following manufacturers' instructions. **Expert Tip:** For the easiest and best grout installation cleanup, use Primo Tool™ Wringmaster grout cleaning system or SpongaUSA™ grout sponges.
5. Most, if not all, of the **Grout Release** residue should be removed/eliminated during the normal grout installation cleanup process. If **Grout Release** residue remains on surface, use **OMNI Heavy Duty Cleaner** to remove (see OMNI Product Recommendation Guide). **Expert Tip:** For most smooth porous surfaces, an application of **OMNI Elite Sealer** or **OMNI Enhancing Sealer** provides excellent pre-grout protection from mortar and grout stains and makes the installation and cleanup of grout easier.

SIZES:

Gallons (other sizes available by special order).

COVERAGE:

Approx. 300 to 600 sq. ft. (27.9m² to 55.7m²) per gallon depending on the type of surface, porosity, texture, temperature and method of application.

TECHNICAL SUPPORT:

Call 949-709-5270, Monday thru Friday, 6:00am PT to 4:00pm PT or e-mail TechSupport@OMNI-Sealers.com.

COMPLIANCE AND HANDLING:

- Complies with all Federal, State and Local VOC regulatory requirements.
- Use and store between 40°F and 100°F (4°C and 38°C).
- Store in original container only and close after each use.
- Shelf life expected to be at least 1 year.

LIMITATIONS:

- Prevent product from contacting surrounding surfaces such as carpet, glass, landscaping, metal, paint and wood.
- Prevent build-up of **Grout Release** in grout joints.

WARNINGS:

MAY BE HARMFUL IF SWALLOWED. MAY IRRITATE EYES AND SKIN. Wear skin and eye protection. If product gets in eyes, flush with water for at least 15 minutes. If product gets on skin, wash with soap and water. If irritation persists, seek medical attention. If swallowed, DO NOT induce vomiting, seek medical attention.

KEEP OUT OF REACH OF CHILDREN

WARRANTY:

100% SATISFACTION GUARANTEED, when used as directed. Contact OMNI Sealers for exclusive remedy of either refund of purchase price or replacement of product. Proof of purchase within one year of purchase, required. Determining suitability of product for intended use shall be solely the responsibility of the user. There are no warranties, expressed or implied, including those of merchantability or fitness for a particular purpose, which is beyond the product description. In no case shall OMNI be liable for incidental or consequential damages.