

# Low Gloss Sealer

## TECHNICAL DATA SHEET



### PRODUCT BENEFITS:

- Excellent Stain Protection from Water-based and Oil-based Contaminates.
- Innovative Water-based Technology provides an Extremely Durable Low Gloss Coating.
- Unique Formula Allows Moisture Vapor Transmission.
- Unaffected by Ultra-Violet Light.

### USES:

- Unglazed Tile such as Ceramic, Porcelain and Quarry, including smooth and dense.
- Porous Natural Stone such as Limestone, Slate, Soapstone and Travertine.
- Concrete and Masonry surfaces such as Adobe, Brick, Pavers, Saltillo, and Terra Cotta.
- Sanded and Non-Sanded Cement Grouts.
- Interior and Exterior applications.

Can also be used as a Pre-Grouting sealer

### DIRECTIONS:

Read entire label before using. Use only as directed. **Always Test** in a small inconspicuous area with a 24-hour cure time to determine ease of application and desired results. Allow new grout installations to cure for at least 48 hours prior to application. Be sure surface is clean, thoroughly dry and free of sealers, coatings and contaminants before sealing.

### SURFACE PREPARATION/REMOVAL:

- Existing Sealers – **OMNI Sealer Remover**.
- Existing Coatings/Waxes – **OMNI Heavy Duty Cleaner** or **OMNI Elite Cleaner**.
- Existing Contaminates - **OMNI Buffer Acid Cleaner**, **OMNI Efflorescence Remover**, **OMNI Elite Cleaner**, **OMNI Deep Cleaner**, **OMNI Poultice Stain Remover** or **OMNI Sulfamic Acid Cleaner**.

### APPLICATION STEPS:

1. Apply thin, even, overlapping coats of **Low Gloss Sealer** using a SpongaUSA™ Sealer sponge, or a paint-pad applicator, soft brush or sprayer.
2. Most surfaces require 2 or more coats of **Low Gloss Sealer**.
3. Allow at least 30 minutes drying time between coats.
4. Surface is ready for traffic in 12 hours after final coat. Keep area dry for at least 24 hours.

Expert Tip: If over time, heavy traffic and/or maintenance methods alter **Low Gloss Sealer's** gloss or appearance, additional coats can be applied, as product will easily and effectively bond to itself.

### SIZES:

Quarts, Gallons (other sizes available by special order).

### COVERAGE:

Approx. 300 to 1000 sq. ft. (27.9m<sup>2</sup> to 92.9 m<sup>2</sup>) per coat per gallon depending on the type of surface, porosity, texture, temperature, method of application and number of coats.

### TECHNICAL SUPPORT:

Call 949-709-5270, Monday thru Friday, 6:00am PT to 4:00pm PT or e-mail [TechSupport@OMNI-Sealers.com](mailto:TechSupport@OMNI-Sealers.com).

### EXPECTED WEAR:

Up to 3 years depending on type, density and texture of sealed surface. Foot traffic, cleaning methods and weather conditions can also affect wear.

### MAINTENANCE:

- Routine Cleaning – **OMNI Concentrated Cleaner**.
- Periodic/Strong Cleaning – **OMNI Heavy Duty Cleaner** or **OMNI Deep Cleaner**.
- Problem Solving – **OMNI Buffer Acid Cleaner**, **OMNI Efflorescence Remover**, **OMNI Elite Cleaner**, **OMNI Poultice Stain Remover** or **OMNI Sulfamic Acid Cleaner**.

### COMPLIANCE AND HANDLING:

- Complies with all Federal, State and Local VOC regulatory requirements.
- Use and store between 40°F and 100°F (4°C and 38°C).
- Store in original container only and close after each use.
- Shelf life expected to be at least 1 year.

### LIMITATIONS:

- Not recommended for areas subject to standing water such as pools, spas, showers, etc.
- Harsh cleaners containing ammonia bleach, high-acid, high-alkaline or solvents can affect sealer's performance.
- Prevent sealer from contacting surrounding surfaces such as carpet, glass, landscaping, paint, metal and wood.
- Protect unused, stored product from freezing.

### WARNINGS:

MAY BE HARMFUL IF SWALLOWED. MAY IRRITATE EYES AND SKIN. Wear skin and eye protection. If product gets in eyes, flush with water for at least 15 minutes. If product gets on skin, wash with soap and water. If irritation persists, seek medical attention. If swallowed, DO NOT induce vomiting, seek medical attention.

### KEEP OUT OF REACH OF CHILDREN

### WARRANTY:

100% SATISFACTION GUARANTEED, when used as directed. Contact OMNI Sealers for exclusive remedy of either refund of purchase price or replacement of product. Proof of purchase within one year of purchase, required. Determining suitability of product for intended use shall be solely the responsibility of the user. There are no warranties, expressed or implied, including those of merchantability or fitness for a particular purpose, which is beyond the product description. In no case shall OMNI be liable for incidental or consequential damages.