

SEALING GUIDE

Adoquin / Cantera Stone

Classification: Geological. Metamorphic formation; siliceous.

Description: Volcanic quartz-based stone containing a variety of colored aggregates and pumice in a silica quartz matrix.

Density: Soft (4 to 5 MOH).






Porosity: Highly Porous (>7.0%).

Uses: Interior walls and floors. Exterior paving in mild climate.

Other: Primarily quarried in Mexico. Available in multiple colors.



SEALERS

DESIRED RESULTS	OMNI OPTIONS	BENEFITS	EXP. WEAR	COATS	APPROX. COVERAGE	INT.	EXT.
NATURAL APPEARANCE AND PREMIUM STAIN RESISTANCE		<ul style="list-style-type: none"> • MAXIMUM STAIN PROTECTION, ESPECIALLY IN FOOD PREP AND SERVICE AREAS. • PRESERVES THE NATURAL APPEARANCE OF THE SURFACE. • MAKES ON-GOING MAINTENANCE EASIER. 	15 YRS.	2	400 - 600 SQ. FT. PER COAT PER GALLON	YES	YES
ENHANCED APPEARANCE AND PREMIUM STAIN RESISTANCE		<ul style="list-style-type: none"> • MAXIMUM STAIN PROTECTION, ESPECIALLY IN FOOD PREP AND SERVICE AREAS. • DARKENS, REJUVENATES, HIGHLIGHTS AND ENHANCES UNSEALED SURFACES. • HIGHLY FADE-RESISTANT. 	15 YRS.	1 - 2	500 - 700 SQ. FT. PER COAT PER GALLON	YES	YES
LOW GLOSS APPEARANCE AND EXCELLENT STAIN RESISTANCE		<ul style="list-style-type: none"> • EXCELLENT STAIN PROTECTION. • HIGHLY DURABLE LOW GLOSS SURFACE. • BONDS TO ITSELF FOR TOUCH-UP AND REAPPLICATION. 	3 YRS.	2 - 3	400 - 600 SQ. FT. PER COAT PER GALLON	YES	YES
HIGH GLOSS APPEARANCE AND EXCELLENT STAIN RESISTANCE		<ul style="list-style-type: none"> • EXCELLENT STAIN PROTECTION. • HIGHLY DURABLE HIGH GLOSS SURFACE. • BONDS TO ITSELF FOR TOUCH-UP AND REAPPLICATION. 	3 YRS.	2 - 3	400 - 600 SQ. FT. PER COAT PER GALLON	YES	NO
NATURAL APPEARANCE AND ECONOMICAL STAIN RESISTANCE		<ul style="list-style-type: none"> • ECONOMICAL STAIN PROTECTION, PRESERVES NATURAL APPEARANCE. • STAIN RESISTANCE FROM MOST CONTAMINATES. • MAKES ON-GOING MAINTENANCE EASIER. 	3 YRS.	2	400 - 600 SQ. FT. PER COAT PER GALLON	YES	YES

EXPERT TIP: At least 2 hours prior to grout installation, apply at least one coat of the “desired results” OMNI Sealer to surface as a **Pre-Grout Sealer**. Makes grout installation and clean-up easier and faster, while protecting surface from grout stains. Allow new grout to cure at least 48 hours prior applying “desired results” OMNI Sealer.

Technical Support: 949-709-5270 Mon thru Fri 6:00am PT to 4:00pm PT and/or E-mail TechSupport@OMNI-Sealers.com

ALWAYS TEST IN A SMALL INCONSPICUOUS AREA.