

# SEALING GUIDE

## Granite – Quartz Based (Exotics)

**Classification:** Geological. Metamorphic formation; siliceous.

**Description:** Crystalline quartz particles matrix with igneous characteristics and banding similar to veins.

**Density:** Hard (6 - 7 MOH).






**Porosity:** Slightly Porous (0.5% to 3.0%) to Moderately Porous (3.0% to 7.0%).

**Uses:** Interior walls, floors and countertops. Exterior veneer (cladding).

**Other:** Exotic granite can be brittle, limited tooling and edge detail option on countertops.



## SEALERS

| DESIRED RESULTS                                      | OMNI OPTIONS  | BENEFITS   | EXP. WEAR | COATS | APPROX. COVERAGE                        | INT. | EXT. |
|--|---|--|-----------|-------|---|------|------|
| NATURAL APPEARANCE AND PREMIUM STAIN RESISTANCE      |    | <ul style="list-style-type: none"> <li>• MAXIMUM STAIN PROTECTION, ESPECIALLY IN FOOD PREP AND SERVICE AREAS.</li> <li>• PRESERVES THE NATURAL APPEARANCE OF THE SURFACE.</li> <li>• MAKES ON-GOING MAINTENANCE EASIER.</li> </ul>     | 15 YRS.   | 1 - 2 | 700 - 1,000 SQ. FT. PER COAT PER GALLON | YES  | YES  |
| ENHANCED APPEARANCE AND PREMIUM STAIN RESISTANCE     |    | <ul style="list-style-type: none"> <li>• MAXIMUM STAIN PROTECTION, ESPECIALLY IN FOOD PREP AND SERVICE AREAS.</li> <li>• DARKENS, REJUVENATES, HIGHLIGHTS AND ENHANCES UNSEALED SURFACES.</li> <li>• HIGHLY FADE-RESISTANT.</li> </ul> | 15 YRS.   | 1     | 800 - 1,100 SQ. FT. PER COAT PER GALLON | YES  | YES  |
| LOW GLOSS APPEARANCE AND EXCELLENT STAIN RESISTANCE  |    | <ul style="list-style-type: none"> <li>• EXCELLENT STAIN PROTECTION.</li> <li>• HIGHLY DURABLE LOW GLOSS SURFACE.</li> <li>• BONDS TO ITSELF FOR TOUCH-UP AND REAPPLICATION.</li> </ul>  | 3 YRS.    | 2     | 700 - 1,000 SQ. FT. PER COAT PER GALLON | YES  | YES  |
| HIGH GLOSS APPEARANCE AND EXCELLENT STAIN RESISTANCE |   | <ul style="list-style-type: none"> <li>• EXCELLENT STAIN PROTECTION.</li> <li>• HIGHLY DURABLE HIGH GLOSS SURFACE.</li> <li>• BONDS TO ITSELF FOR TOUCH-UP AND REAPPLICATION.</li> </ul>   | 3 YRS.    | 2     | 700 - 1,000 SQ. FT. PER COAT PER GALLON | YES  | NO   |
| NATURAL APPEARANCE AND ECONOMICAL STAIN RESISTANCE   |  | <ul style="list-style-type: none"> <li>• ECONOMICAL STAIN PROTECTION, PRESERVES NATURAL APPEARANCE.</li> <li>• STAIN RESISTANCE FROM MOST CONTAMINATES.</li> <li>• MAKES ON-GOING MAINTENANCE EASIER.</li> </ul>                       | 3 YRS.    | 2     | 700 - 1,000 SQ. FT. PER COAT PER GALLON | YES  | YES  |

**EXPERT TIP:** At least 2 hours prior to grout installation, apply at least one coat of the “desired results” OMNI Sealer to surface as a **Pre-Grout Sealer**. Makes grout installation and clean-up easier and faster, while protecting surface from grout stains. Allow new grout to cure at least 48 hours prior applying “desired results” OMNI Sealer.

**Technical Support:** 949-709-5270 Mon thru Fri 6:00am PT to 4:00pm PT and/or E-mail [TechSupport@OMNI-Sealers.com](mailto:TechSupport@OMNI-Sealers.com)

**ALWAYS TEST IN A SMALL INCONSPICUOUS AREA.**