

SEALING GUIDE

Marble – Honed

Classification: Geological. Metamorphic formation; calcareous.

Description: Composed predominantly of crystalline grains of calcite.

Density: Medium (4 – 5) MOH).






Porosity: Slightly Porous (0.5% to 3.0%) to Moderately Porous (3.0% to 7.0%).

Uses: Interior walls, floors and countertops. Exterior limited to mild climate.

Other: Matte finish (little or no gloss) achieve through chemicals, abrasives and machinery. May etch or lighten, if exposed to acid.



SEALERS

| DESIRED RESULTS | OMNI OPTIONS | BENEFITS | EXP. WEAR | COATS | APPROX. COVERAGE | INT. | EXT. |
|------------------------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|-------|-----------------------------------------|------|------|
| NATURAL APPEARANCE AND PREMIUM STAIN RESISTANCE |  | <ul style="list-style-type: none"> • MAXIMUM STAIN PROTECTION, ESPECIALLY IN FOOD PREP AND SERVICE AREAS. • PRESERVES THE NATURAL APPEARANCE OF THE SURFACE. • MAKES ON-GOING MAINTENANCE EASIER. | 15 YRS. | 2 | 700 - 1,000 SQ. FT. PER COAT PER GALLON | YES | YES |
| ENHANCED APPEARANCE AND PREMIUM STAIN RESISTANCE |  | <ul style="list-style-type: none"> • MAXIMUM STAIN PROTECTION, ESPECIALLY IN FOOD PREP AND SERVICE AREAS. • DARKENS, REJUVENATES, HIGHLIGHTS AND ENHANCES UNSEALED SURFACES. • HIGHLY FADE-RESISTANT. | 15 YRS. | 1 - 2 | 800 - 1,200 SQ. FT. PER COAT PER GALLON | YES | YES |
| LOW GLOSS APPEARANCE AND EXCELLENT STAIN RESISTANCE |  | <ul style="list-style-type: none"> • EXCELLENT STAIN PROTECTION. • HIGHLY DURABLE LOW GLOSS SURFACE. • BONDS TO ITSELF FOR TOUCH-UP AND REAPPLICATION. | 3 YRS. | 2 | 700 - 1,000 SQ. FT. PER COAT PER GALLON | YES | YES |
| HIGH GLOSS APPEARANCE AND EXCELLENT STAIN RESISTANCE |  | <ul style="list-style-type: none"> • EXCELLENT STAIN PROTECTION. • HIGHLY DURABLE HIGH GLOSS SURFACE. • BONDS TO ITSELF FOR TOUCH-UP AND REAPPLICATION. | 3 YRS. | 2 | 700 - 1,000 SQ. FT. PER COAT PER GALLON | YES | NO |
| NATURAL APPEARANCE AND ECONOMICAL STAIN RESISTANCE |  | <ul style="list-style-type: none"> • ECONOMICAL STAIN PROTECTION, PRESERVES NATURAL APPEARANCE. • STAIN RESISTANCE FROM MOST CONTAMINATES. • MAKES ON-GOING MAINTENANCE EASIER. | 3 YRS. | 2 | 700 - 1,000 SQ. FT. PER COAT PER GALLON | YES | YES |

EXPERT TIP: At least 2 hours prior to grout installation, apply at least one coat of the “desired results” OMNI Sealer to surface as a **Pre-Grout Sealer**. Makes grout installation and clean-up easier and faster, while protecting surface from grout stains. Allow new grout to cure at least 48 hours prior applying “desired results” OMNI Sealer.

Technical Support: 949-709-5270 Mon thru Fri 6:00am PT to 4:00pm PT and/or E-mail TechSupport@OMNI-Sealers.com

ALWAYS TEST IN A SMALL INCONSPICUOUS AREA.