

Back-To-New Grout Cleaner

TECHNICAL DATA SHEET



PRODUCT BENEFITS:

- Proprietary Surfactants “lift” Below Surface Contaminates.
- Restores Dirty, Neglected Grout to Like New Appearances.
- Equally Effective on Cement, Epoxy and Urethane Grout.
- Buffered Acids Dissolve Ground-In Dirt and Stains.

USES:

- Cement, Epoxy and Urethane Grout.
- Can also be used to make dirty neglected ceramic, porcelain and quarry tile look new.
- Removes contaminants and stains from Food & Beverage Stains, Grease, Soap Scum, Minerals and Hard Water Deposits, Ground-in Dirt & Soil and more.
- Prepares Grout Joints for the Application of Grout Re-Coloring Sealer and Grout Sealer.
- Interior and Exterior applications.

DIRECTIONS:

Read entire label before using. Use only as directed. Always test in a small inconspicuous area to determine ease of application and desired results (see Limitations below).

APPLICATION STEPS:

1. Sweep or vacuum surface to be cleaned to remove any loose contaminants.
2. Apply **Back-To-New Grout Cleaner** liberally with trigger spray bottle.
Expert Tip: For large projects, it is recommended that the working area be divided into manageable sections of approximately 25 sq. ft.
3. Allow **Back-To-New Grout Cleaner** to dwell on surface for 5 to 10 minutes. Make sure product does not dry on the surface. If needed, apply additional product on the surface.
4. Agitate with a Primo Tools™ White Nylon Scrub Pad or other comparable non-marring scrubbing tool until surface is clean.
5. Thoroughly rinse surface with water. A wet/dry vacuum may also be used.
6. Some surfaces may require additional applications.
Expert Tip: High-pressure (1000-3000 psi) sprayers are highly effective at rinsing away stains when used in conjunction with **Back-To-New Grout Cleaner**.
7. Wipe surface completely dry using a clean, dry, white cotton or micro-fiber towel.
8. If surface is to be sealed, allow 24 hours drying time prior to applying a high quality OMNI sealer (see OMNI Product Recommendation Guide).
Expert Tip: Should **Back-To-New Grout Cleaner** fail to provide desired results to severely discolored grout due to years of neglect, **OMNI Grout Re-Coloring Sealer** is recommended.

SIZES:

32 oz. Trigger Spray (other sizes available by special order).

COVERAGE:

Approx. 33 to 100 sq. ft. (3.1m² to 9.3m²) per 32 ounces depending on the type of surface, porosity, texture, temperature and method of application.

TECHNICAL SUPPORT:

Call 949-709-5270, Monday thru Friday, 6:00am PT to 4:00pm PT or e-mail TechSupport@OMNI-Sealers.com 24/7.

COMPLIANCE AND HANDLING:

- Complies with all Federal, State and Local VOC regulatory requirements.
- Use and store between 40°F and 100°F (4°C and 38°C).
- Store in original container only and close after each use.
- Shelf life expected to be at least 1 year.

LIMITATIONS:

- May etch, lighten, or alter the color of cement-based surfaces, metal, natural stone (such as marble, limestone and other acid sensitive stones) and tile.
- Do not mix with ammoniated cleaners or bleach as harmful fumes may result.
- Prevent product from contacting surrounding surfaces such as carpet, glass, landscaping, metal, paint and wood.

WARNINGS:

MAY BE HARMFUL IF SWALLOWED. MAY IRRITATE EYES AND SKIN. Wear skin and eye protection. If product gets in eyes, flush with water for at least 15 minutes. If product gets on skin, wash with soap and water. If irritation persists, seek medical attention. If swallowed, DO NOT induce vomiting, seek medical attention.

KEEP OUT OF REACH OF CHILDREN

WARRANTY:

100% SATISFACTION GUARANTEED, when used as directed. Contact OMNI Sealers for exclusive remedy of either refund of purchase price or replacement of product. Proof of purchase within one year of purchase, required. Determining suitability of product for intended use shall be solely the responsibility of the user. There are no warranties, expressed or implied, including those of merchantability or fitness for a particular purpose, which is beyond the product description. In no case shall OMNI be liable for incidental or consequential damages.