

# SEALING GUIDE

## Concrete Tile

**Classification:** Manufactured - Factory.

**Description:** Made w/variety of components incl. cement and aggregates (marble powder). Can be dry pressed or fired in a kiln.

**Density:** Medium.

**Porosity:** Moderately Porous (3.0% - 7.0%) to Highly Porous (>7.0%).

**Uses:** Interior walls, floors and countertops. Exterior applications limited to mild climate.

**Other:** Multiple texture options are available. May be susceptible to contaminants and stains.



## SEALERS

| DESIRED RESULTS                                      | OMNI OPTIONS                                                                        | BENEFITS                                                                                                                                                                                                                               | EXP. WEAR | COATS | APPROX. COVERAGE                      | INT. | EXT. |
|------------------------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|-------|---------------------------------------|------|------|
| NATURAL APPEARANCE AND PREMIUM STAIN RESISTANCE      |    | <ul style="list-style-type: none"> <li>• MAXIMUM STAIN PROTECTION, ESPECIALLY IN FOOD PREP AND SERVICE AREAS.</li> <li>• PRESERVES THE NATURAL APPEARANCE OF THE SURFACE.</li> <li>• MAKES ON-GOING MAINTENANCE EASIER.</li> </ul>     | 15 YRS.   | 2     | 400 - 800 SQ. FT. PER COAT PER GALLON | YES  | YES  |
| ENHANCED APPEARANCE AND PREMIUM STAIN RESISTANCE     |    | <ul style="list-style-type: none"> <li>• MAXIMUM STAIN PROTECTION, ESPECIALLY IN FOOD PREP AND SERVICE AREAS.</li> <li>• DARKENS, REJUVENATES, HIGHLIGHTS AND ENHANCES UNSEALED SURFACES.</li> <li>• HIGHLY FADE-RESISTANT.</li> </ul> | 15 YRS.   | 1 - 2 | 500 - 900 SQ. FT. PER COAT PER GALLON | YES  | YES  |
| LOW GLOSS APPEARANCE AND EXCELLENT STAIN RESISTANCE  |    | <ul style="list-style-type: none"> <li>• EXCELLENT STAIN PROTECTION.</li> <li>• HIGHLY DURABLE LOW GLOSS SURFACE.</li> <li>• BONDS TO ITSELF FOR TOUCH-UP AND REAPPLICATION.</li> </ul>                                                | 3 YRS.    | 2 - 3 | 400 - 800 SQ. FT. PER COAT PER GALLON | YES  | YES  |
| HIGH GLOSS APPEARANCE AND EXCELLENT STAIN RESISTANCE |   | <ul style="list-style-type: none"> <li>• EXCELLENT STAIN PROTECTION.</li> <li>• HIGHLY DURABLE HIGH GLOSS SURFACE.</li> <li>• BONDS TO ITSELF FOR TOUCH-UP AND REAPPLICATION.</li> </ul>                                               | 3 YRS.    | 2 - 3 | 400 - 800 SQ. FT. PER COAT PER GALLON | YES  | NO   |
| NATURAL APPEARANCE AND ECONOMICAL STAIN RESISTANCE   |  | <ul style="list-style-type: none"> <li>• ECONOMICAL STAIN PROTECTION, PRESERVES NATURAL APPEARANCE.</li> <li>• STAIN RESISTANCE FROM MOST CONTAMINATES.</li> <li>• MAKES ON-GOING MAINTENANCE EASIER.</li> </ul>                       | 3 YRS.    | 2     | 400 - 800 SQ. FT. PER COAT PER GALLON | YES  | YES  |

**EXPERT TIP:** At least 2 hours prior to grout installation, apply at least one coat of the “desired results” OMNI Sealer to surface as a **Pre-Grout Sealer**. Makes grout installation and clean-up easier and faster, while protecting surface from grout stains. Allow new grout to cure at least 48 hours prior applying “desired results” OMNI Sealer.

Technical Support: 949-709-5270 Mon thru Fri 6:00am PT to 4:00pm PT and/or E-mail [TechSupport@OMNI-Sealers.com](mailto:TechSupport@OMNI-Sealers.com)

**ALWAYS TEST IN A SMALL INCONSPICUOUS AREA.**