

SEALING GUIDE

Porcelain - Certified

Classification: Manufactured - Factory.

Description: Made with at least 50% feldspar clay and fired at high temperature. Can be glazed or unglazed.

Density: Hard (7 - 8 MOH).

Porosity: Non-Porous (<0.5%).

Uses: Interior walls, floors and countertops. Exterior paving and veneer (cladding). Wet areas.

Other: Porcelain tile may be susceptible to grout staining during installation.



SEALERS

DESIRED RESULTS	OMNI OPTIONS	BENEFITS	EXP. WEAR	COATS	APPROX. COVERAGE	INT.	EXT.
NATURAL APPEARANCE AND PREMIUM STAIN RESISTANCE	 	• MAXIMUM STAIN PROTECTION, ESPECIALLY IN FOOD PREP AND SERVICE AREAS. • PRESERVES THE NATURAL APPEARANCE OF THE SURFACE. • MAKES ON-GOING MAINTENANCE EASIER.	15 YRS.	2	1,200 - 1,500 SQ. FT. PER COAT PER GALLON	YES	YES
ENHANCED APPEARANCE AND PREMIUM STAIN RESISTANCE	 	• MAXIMUM STAIN PROTECTION, ESPECIALLY IN FOOD PREP AND SERVICE AREAS. • DARKENS, REJUVENATES, HIGHLIGHTS AND ENHANCES UNSEALED SURFACES. • HIGHLY FADE-RESISTANT.	15 YRS.	1 - 2	1,300 - 1,500 SQ. FT. PER COAT PER GALLON	YES	YES
LOW GLOSS APPEARANCE AND EXCELLENT STAIN RESISTANCE	 	• EXCELLENT STAIN PROTECTION. • HIGHLY DURABLE LOW GLOSS SURFACE. • BONDS TO ITSELF FOR TOUCH-UP AND REAPPLICATION.	3 YRS.	2	1,200 - 1,500 SQ. FT. PER COAT PER GALLON	YES	YES
HIGH GLOSS APPEARANCE AND EXCELLENT STAIN RESISTANCE	 	• EXCELLENT STAIN PROTECTION. • HIGHLY DURABLE HIGH GLOSS SURFACE. • BONDS TO ITSELF FOR TOUCH-UP AND REAPPLICATION.	3 YRS.	2	1,200 - 1,500 SQ. FT. PER COAT PER GALLON	YES	NO
NATURAL APPEARANCE AND ECONOMICAL STAIN RESISTANCE	 	• ECONOMICAL STAIN PROTECTION, PRESERVES NATURAL APPEARANCE. • STAIN RESISTANCE FROM MOST CONTAMINATES. • MAKES ON-GOING MAINTENANCE EASIER.	3 YRS.	2	1,200 - 1,500 SQ. FT. PER COAT PER GALLON	YES	YES

EXPERT TIP: At least 2 hours prior to grout installation, apply at least one coat of the “desired results” OMNI Sealer to surface as a **Pre-Grout Sealer**. Makes grout installation and clean-up easier and faster, while protecting surface from grout stains. Allow new grout to cure at least 48 hours prior applying “desired results” OMNI Sealer.

Technical Support: 949-709-5270 Mon thru Fri 6:00am PT to 4:00pm PT and/or E-mail TechSupport@OMNI-Sealers.com

ALWAYS TEST IN A SMALL INCONSPICUOUS AREA.