## **SEALING GUIDE**

## **Cement Grout**

Classification: Manufactured – Job site.

**Description:** Mixture of cement, aggregates, additives and pigments.

Density: Soft to Medium.

**Porosity:** Slightly Porous (0.5% to 3.0%) to Moderately Porous (3.0% to 7.0%).

Uses: Installed between Adjoining Tiles and Stones. Walls, Floors and Countertops. Interior and Exterior. Wet areas.

Other: Sanded for wide joints (>1/8"). Unsanded for narrow joints (<1/8").



SEALERS							
DESIRED RESULTS	OMNI OPTIONS	BENEFITS	EXP. WEAR	COATS	APPROX. COVERAGE	INT.	EXT.
NATURAL APPEARANCE AND PREMIUM STAIN RESISTANCE	GROUT ADDITIVE SEALER	<ul> <li>MAXIMUM STAIN PROTECTION FOR GROUT, PRESERVES NEW APPEARANCE.</li> <li>BUILT-IN STAIN RESISTANCE FROM ALL TYPES OF CONTAMINATES.</li> <li>MAKES GROUT JOINTS STRONGER/DENSER AND ON-GOING MAINTENANCE EASIER.</li> </ul>	LIFETIME	INCL.	70 OZ PER 25# BAG SANDED GROUT	YES	YES
NATURAL APPEARANCE AND PREMIUM STAIN RESISTANCE	SEALER SAIR	<ul> <li>MAXIMUM STAIN PROTECTION, ESPECIALLY IN FOOD PREP AND SERVICE AREAS.</li> <li>PRESERVES THE NATURAL APPEARANCE OF THE SURFACE.</li> <li>MAKES ON-GOING MAINTENANCE EASIER.</li> </ul>	<b>15 Y</b> RS.	2	200 - 1,200 SQ. FT. PER COAT PER QUART	YES	YES
ENHANCED APPEARANCE AND PREMIUM STAIN RESISTANCE	ENHANCING SEALER	<ul> <li>MAXIMUM STAIN PROTECTION, ESPECIALLY IN FOOD PREP AND SERVICE AREAS.</li> <li>DARKENS, REJUVENATES, HIGHLIGHTS AND ENHANCES UNSEALED SURFACES.</li> <li>HIGHLY FADE-RESISTANT.</li> </ul>	15 Yrs.	1-2	200 - 1,200 SQ. FT. PER COAT PER QUART	YES	YES
RE-COLOR GROUT AND PREMIUM STAIN RESISTANCE	GROUT RECOLORING SEALER	<ul> <li>REJUVENATES STAINED, FADED AND/OR DISCOLORED GROUT.</li> <li>MAXIMUM STAIN PROTECTION WITH UNIFORM COLOR – 40 COLORS AVAILABLE.</li> <li>MAKES ON-GOING MAINTENANCE EASIER.</li> </ul>	15 Yrs.	1-2	50 - 300 SQ. FT. PER COAT PER 8 OZ	YES	YES
NATURAL APPEARANCE AND ECONOMICAL STAIN RESISTANCE	GROUT SEALER	<ul> <li>ECONOMICAL STAIN PROTECTION, PRESERVES NATURAL APPEARANCE.</li> <li>STAIN RESISTANCE FROM MOST CONTAMINATES.</li> <li>MAKES ON-GOING MAINTENANCE EASIER.</li> </ul>	5 Yrs.	2	200 - 1,200 SQ. FT. PER COAT PER QUART	YES	YES
NATURAL APPEARANCE AND ECONOMICAL STAIN RESISTANCE	SEALER	<ul> <li>ECONOMICAL STAIN PROTECTION, PRESERVES NATURAL APPEARANCE.</li> <li>STAIN RESISTANCE FROM MOST CONTAMINATES.</li> <li>MAKES ON-GOING MAINTENANCE EASIER.</li> </ul>	3 Yrs.	2	200 - 1,200 SQ. FT. PER COAT PER QUART	YES	YES

CEALEDO

**EXPERT TIP:** When installing new grout, OMNI **Grout Additive Sealer** is always recommended as it provides built-in lifetime stain protection for sanded and non-sanded cement grout.

Technical Support: 949-709-5270 Mon thru Fri 6:00am PT to 4:00pm PT and/or E-mail TechSupport@OMNI-Sealers.com.

ALWAYS TEST IN A SMALL INCONSPICUOUS AREA.

<sup>\*</sup>NOTE: When the surface surrounding a cement grout joint is sealed with an OMNI sealer in accordance to recommendations, there is no need to apply additional sealer directly to the grout joint.