

# SEALING GUIDE (RE-COLORING)

## Epoxy Grout

**Classification:** Manufactured – Job site.

**Description:** Made from epoxy resins and filler powder (can include sand)

**Density:** Medium.



**Porosity:** Non-porous.

**Uses:** Interior and Exterior walls, countertops, and floors. Wet areas.

**Other:** Limitation in grout widths.



## SEALERS

DESIRED RESULTS	OMNI OPTIONS	BENEFITS	EXP. WEAR	COATS	APPROX. COVERAGE	INT.	EXT.
RE-COLOR GROUT AND PREMIUM STAIN RESISTANCE	 	<ul style="list-style-type: none"> <li>• REJUVENATES STAINED, FADED AND/OR DISCOLORED GROUT.</li> <li>• MAXIMUM STAIN PROTECTION WITH UNIFORM COLOR – 40 COLORS AVAILABLE.</li> <li>• MAKES ON-GOING MAINTENANCE EASIER.</li> </ul>	15 YRS.	1 - 2	50 - 300 SQ. FT. PER COAT PER 8 OZ	YES	YES

Technical Support: 949-709-5270 Mon thru Fri 6:00am PT to 4:00pm PT and/or E-mail [TechSupport@OMNI-Sealers.com](mailto:TechSupport@OMNI-Sealers.com).

ALWAYS TEST IN A SMALL INCONSPICUOUS AREA.