## SEALING GUIDE

## Terrazzo Poured In Place - Cement

Classification: Manufactured - Job site.

**Description:** Mix of granite, marble and/or glass chips (70.0%) imbedded in a cement matrix. Ground/finished after setting

Density: Medium.

**Porosity:** Moderately Porous (3.0% to 7.0%) to Highly Porous (>7.0%). Binder affects porosity.

**Uses:** Interior floors.

**Other:** Will have the same characteristic as the stone used in the matrix.



SEALENS							
DESIRED RESULTS	OMNI OPTIONS	BENEFITS	EXP. WEAR	COATS	APPROX. COVERAGE	INT.	EXT.
NATURAL APPEARANCE AND PREMIUM STAIN RESISTANCE	SEALER SEALER	<ul> <li>MAXIMUM STAIN PROTECTION, ESPECIALLY IN FOOD PREP AND SERVICE AREAS.</li> <li>PRESERVES THE NATURAL APPEARANCE OF THE SURFACE.</li> <li>MAKES ON-GOING MAINTENANCE EASIER.</li> </ul>	15 Yrs.	2	600 - 800 SQ. FT. PER COAT PER GALLON	YES	YES
ENHANCED APPEARANCE AND PREMIUM STAIN RESISTANCE	SEALER	<ul> <li>MAXIMUM STAIN PROTECTION, ESPECIALLY IN FOOD PREP AND SERVICE AREAS.</li> <li>DARKENS, REJUVENATES, HIGHLIGHTS AND ENHANCES UNSEALED SURFACES.</li> <li>HIGHLY FADE-RESISTANT.</li> </ul>	<b>15 Y</b> RS.	1 - 2	700 - 900 SQ. FT. PER COAT PER GALLON	YES	YES
LOW GLOSS APPEARANCE AND EXCELLENT STAIN RESISTANCE	LOW GLOSS SEALER	<ul> <li>Excellent Stain Protection.</li> <li>Highly Durable Low Gloss Surface.</li> <li>Bonds to Itself for Touch-up and Reapplication.</li> </ul>	3 Yrs.	2-3	600 - 800 SQ. FT. PER COAT PER GALLON	YES	YES
HIGH GLOSS APPEARANCE AND EXCELLENT STAIN RESISTANCE	HIGH GLOSS	<ul> <li>Excellent Stain Protection.</li> <li>Highly Durable High Gloss Surface.</li> <li>Bonds to Itself for Touch-up and Reapplication.</li> </ul>	3 Yrs.	2-3	600 - 800 SQ. FT. PER COAT PER GALLON	YES	No
NATURAL APPEARANCE AND ECONOMICAL STAIN RESISTANCE	SEALER	<ul> <li>ECONOMICAL STAIN PROTECTION, PRESERVES NATURAL APPEARANCE.</li> <li>STAIN RESISTANCE FROM MOST CONTAMINATES.</li> <li>MAKES ON-GOING MAINTENANCE EASIER.</li> </ul>	3 Yrs.	2	600 - 800 SQ. FT. PER COAT PER GALLON	YES	YES

CEALEDC

Technical Support: 949-709-5270 Mon thru Fri 6:00am PT to 4:00pm PT and/or E-mail TechSupport@OMNI-Sealers.com

ALWAYS TEST IN A SMALL INCONSPICUOUS AREA.